

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 256 309 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
13.11.2002 Bulletin 2002/46

(51) Int Cl.7: **A47L 15/50**(21) Application number: **01830299.2**(22) Date of filing: **09.05.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Ambrosi, Andrea**
37052 Casaleone VR (IT)


(74) Representative: **Concone, Emanuele et al**
Società Italiana Brevetti S.p.A.
Via Carducci 8
20123 Milano (IT)

(71) Applicant: **Bonferraro S.p.A.**
37060 Bonferraro (VR) (IT)

(54) Cutlery basket for dishwasher

(57) A cutlery basket for dishwasher includes a containing body (S) of parallelepiped shape open at the top in which there are inserted two mobile partitions (M, M') provided at the bottom end with lateral pins (P) which slide in guide slots (G) formed in the sides of the container (S), at the top end with lateral teeth (N) and at mid-height with recesses (R) orthogonal to the plane of the mobile partition (M, M'), the teeth (N) being insertible

into corresponding vertical seats (V) formed in the top edge (E) of the container (S) while the recesses (R) are shaped to fit over the edge (E). The mobile partitions (M, M') are provided with holes (A) sized for inserting the handles of cutlery and/or the blades of knives and since they can be arranged horizontally even cantilevered outside the edge (E) they allow to increase the basket capacity.

**Fig. 3**

Description

[0001] The present invention relates to cutlery baskets for dishwashers, and in particular to a basket with internal mobile partitions which greatly enhance its possibilities of use.

[0002] It is known that inside a dishwasher, usually in the lower rack, there is placed a cutlery basket wherein the cutlery is held in a substantially vertical position. The conventional basket generally has a grid-like structure (or perforated in some way) of parallelepiped shape, the internal volume being divided into smaller areas by vertical dividing partitions to keep the cutlery upright. Moreover, a top handle is provided to make it easy to be introduced into and removed from the rack, so as to be able to load and unload it conveniently outside the dishwasher.

[0003] Normally there are also available one or more horizontal perforated shelves to be placed on the top edge of the basket, so as to insert the cutlery therein whereby it remains exactly vertical and regularly spaced. In this way an optimum washing is obtained, even though the capacity of the basket is reduced and therefore said horizontal shelves are not always used. However, when the shelves are removed from the basket they have to be stored outside the dishwasher, this resulting in that often they actually are removed and never used again although they could be useful in certain instances.

[0004] Clearly it is also possible to use only one horizontal shelf leaving uncovered the other half of the basket, so as to achieve a compromise between capacity and washing effectiveness. In any case, cutlery can never be placed outside the basket.

[0005] Therefore the object of the present invention is to provide a cutlery basket which overcomes the above-mentioned limits. This object is achieved by means of a cutlery basket provided with internal mobile partitions which can take either a vertical or horizontal position, and in the latter case even partially cantilevered outside the basket. Other advantageous features of the present cutlery basket are specified in the dependent claims.

[0006] The main advantage of the present basket is that it is even possible to arrange cutlery outside the parallelepiped structure by inserting it in the cantilever horizontal shelves, so as to increase the basket capacity.

[0007] Another advantage is that of having the maximum flexibility of use, in that the mobile partitions allow it to take a conventional configuration with vertical partitions, or with horizontal shelves inside or outside the basket in addition to any intermediate configuration (e.g. a vertical partition and a horizontal cantilever shelf).

[0008] Still another advantage stems from the fact that the mobile partitions can be made integral with the basket structure, whereby the user is guided in their positioning through suitable guiding slots and the partitions can not be removed and get lost.

[0009] Further advantages and characteristics of the

cutlery basket according to the present invention will be clear to those skilled in the art from the following detailed description of an embodiment thereof, with reference to the annexed drawings wherein:

Fig. 1 is an exploded perspective view showing the elements which make up a basket according to the invention with two mobile partitions;

Fig. 2 is a perspective view of the basket with the mobile partitions positioned horizontally in the configuration of minimum capacity; and

Fig. 3 is a perspective view of the basket in an intermediate configuration with one mobile partition arranged in a position of vertical dividing wall and the other one arranged in a position of horizontal cantilever shelf.

[0010] With reference to fig. 1, there is seen that the present basket is made up of a containing body S of parallelepiped shape open at the top in which there are inserted a central fixed partition F with a handle H and two mobile partitions M, M'. More specifically, partition F is inserted into a vertical guide L formed between two central ribs and is snap-coupled to container S, whereas the mobile partitions M, M' are provided at the bottom end with lateral pins P which slide along guide slots G formed in the sides of container S. These guides G are substantially shaped as an inverted L, with the horizontal leg extending toward the basket center but also extending outward in the opposite direction slightly beyond the point where the vertical leg branches out.

[0011] The mobile partitions M, M' are also provided at their top end with lateral teeth N, and at mid-height with recesses R orthogonal to the plane of the mobile partition and formed in the sides extending on the face facing outward. Teeth N can be inserted into corresponding vertical seats V formed in raised portions of the top edge E of container S, while recesses R are shaped to fit over said top edge E.

[0012] All the above-mentioned elements S, F, M and M' have a grid-like structure, i.e. a plurality of holes arranged in regular rows to allow the passage of water. In particular, in the case of the mobile partitions M, M' holes A are sized to insert therein the handles of cutlery and/or the blades of knives.

[0013] As clearly illustrated in figs. 2 and 3, the mobile partitions M, M' can be positioned either vertically to act as dividing walls, or horizontally to act as shelves for inserting cutlery therein. In this second use they can be arranged inside container S as in fig. 2, or in a cantilevered manner so as to project halfway outside container S as in fig. 3. In the first case pins P reach the inner end of the horizontal leg of guide G, whereas in the second case they reach the outer end of said leg and recesses R are fit over edge E of container S.

[0014] It should be noted that in the illustrated embodiment the basket height is greater than half its length, whereby when the mobile partition is arranged vertically

it does not touch the basket bottom. Therefore solid ribs D are preferably provided on the basket bottom at seats V, so as to obtain a continuous vertical partition from edge E to the bottom. Moreover there is also preferably provided a solid rib D', still of small height, which longi-

[0015] From the description above it is clear how the basket according to the invention allows, since each mobile partition has 24 holes A, to house from a minimum of 48 spaced pieces of cutlery (fig.2) to a maximum of 48 spaced pieces of cutlery plus all the cutlery which can be contained between the two horizontal cantilever shelves and the central partition F. It should be noted that in this latter case 24 spaced pieces of cutlery are hanging outside container S, thus achieving a substantial increase in the basket capacity.

[0016] It is clear that the above-described and illustrated embodiment of the cutlery basket according to the invention is just an example susceptible of various modifications. In particular, depending on the shape and size of the basket the number of mobile partitions may be greater or lower than two, and the shape of the mobile partitions and the number and arrangement of holes A formed therein may change as well. Also the number of recesses R could be greater than one per side, so as to increase the possibilities of adjustment of the shelf portion projecting from container S. In this case, as a consequence, guide G would take in practice a T shape.

[0017] Similarly, the coupling mechanisms between the mobile partitions and container S may be different from the above-described couplings pin P/guide G, tooth N/seat V and recess R/edge E. For example, the partitions could be vertically inserted into lateral guides same as the central partition F, and then horizontally arranged in similar guides formed in edge E. In this case the partitions would no longer be integral with container S, but it would be possible to adjust at will the extent of the cantilever portion taking the increase in the basket capacity to the maximum.

2. Cutlery basket according to claim 1, **characterized in that** the coupling means make said at least one mobile partition (M) integral with the container (S).
3. Cutlery basket according to claim 2, **characterized in that** the coupling means consist of lateral pins (P) located at the bottom end of the partition (M) which slide in guide slots (G) formed in the sides of the container (S), of lateral teeth (N) located at the top end of the partition (M) and of recesses (R) orthogonal to the plane of the partition (M), said teeth (N) being insertible into corresponding vertical seats (V) formed in the edge (E) of the container (S) while said recesses (R) are shaped to fit over said edge (E).
4. Cutlery basket according to claim 3, **characterized in that** the recesses (R) are formed at mid-height of the partition (M).
5. Cutlery basket according to claim 3 or 4, **characterized in that** along the height of the partition (M) there are formed multiple pairs of recesses (R).
6. Cutlery basket according to claim 5, **characterized in that** the guide slots (G) formed in the container (S) have a T shape.
7. Cutlery basket according to one or more of the preceding claims, **characterized in that** on the bottom of the container (S), at the vertical position of the partition (M), there is arranged a solid rib (D) having a height equal to the difference in height between the container (S) and the partition (M).

Claims

1. Cutlery basket for dishwasher including a containing body (S) of parallelepiped shape open at the top in which there is arranged at least one vertical partition (M), **characterized in that** said at least one partition (M) is provided with a plurality of holes (A) for inserting cutlery and it is mobile between the vertical position inside said container (S) and a plurality of horizontal positions at the top edge (E) of the container (S), in at least one of said positions being arranged at least partially cantilevered outside said edge (E), said mobile partition (M) and the container (S) being provided with coupling means for blocking the mobile partition (M) in each of the positions it can take.




Fig. 1




Fig. 2




Fig. 3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 83 0299

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	FR 2 736 534 A (ELECTROLUX ZANUSSI ELETTRODOME) 17 January 1997 (1997-01-17) * figures *	1	A47L15/50
A	FR 2 240 708 A (MIELE & CIE) 14 March 1975 (1975-03-14) * figures *	1	
A	US 5 431 294 A (STOTTMANN RICHARD L ET AL) 11 July 1995 (1995-07-11) * figures *	1	
A	US 5 287 984 A (MICHAEL DARYL A) 22 February 1994 (1994-02-22) * figures *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A47L
Place of search		Date of completion of the search	Examiner
THE HAGUE		18 October 2001	Debard, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 83 0299

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-2001

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
FR 2736534	A	17-01-1997	IT	PN950031 U1	13-01-1997
			DE	29609973 U1	29-08-1996
			ES	1034677 U1	16-01-1997
			FR	2736534 A1	17-01-1997
			GB	2303055 A , B	12-02-1997
FR 2240708	A	14-03-1975	DE	7329899 U	20-02-1975
			FR	2240708 A1	14-03-1975
			IT	1014581 B	30-04-1977
US 5431294	A	11-07-1995	NONE		
US 5287984	A	22-02-1994	CA	2070020 A1	10-06-1993